



CERTIFICATE FI 27108

Our Ref. 260674-1

Product

Terminal block

Type

VI series

Trade mark

(a)

Certificate Holder/ Manufacturer

Anytek Technology Corp.

Central Industrial Zone Pyng Dih Town, Long Gang District

518117, ShenzhenCity, GUANGDONG

CHINA

Technical information

0,5 to 1,5 mm², 300 V, T 105, IP00

Other information

See the Appendix to this Certificate

The product is certified according to the following standard(s)

EN 60998-2-1:2004

Validity

This certificate is valid until 17 November 2016 unless the standard in question has been amended or superseded with significant changes in requirements, in which case, SGS Fimko has the right to shorten the validity of the certificate based on the legislation of the European Union. This certificate includes the right to use the FI mark under the condition that changes (if any) will be checked at SGS Fimko before the product is brought onto market and that the conditions for FI certification are met.

Directive information

The product(s) fulfils the essential safety requirements for CE conformity marking according to the Low Voltage Directive (2006/95/EC) at the date of issue of the certificate.

Date of issue

17 November 2011

SGS Fimko Ltd

Signature

Sixten Lökfors Project Manager



This certificate is issued by the company under its General Conditions for Certification Services accessible at www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Appendix to Certificate: 27108

Manufacturing site

Anytek Electronic Technology (Shenzhen) Co., Ltd. Central Industrial Zone, Pyng Dih Town, Long Gang District Shenzhen City, 518117, GUANGDONG CHINA

Additional information

Coding for VI series:

$$VI - XX 1) - X 2) - X 3) - X 4) - X 5) - XXXX 6)$$

Code Definition

1) Number of poles

02 2- contacts (basic block)

03 3- contacts (basic block)

(stackable by combination of 2- and 3- contact blocks)

- 2) Pitch
 - 0 5,00 mm
 - 1 10,0 mm
 - 2 5,08 mm
 - 3 10,16 mm
 - 4 7,5 mm
 - 5 15,0 mm
- 3) Screw & Clamp
 - 0 "+/-" Combination type / W/Brass Machined Clamp
 - 1 "+/-" Slot type / W/Brass Machined Clamp
- 4) Color
 - 5 Green
- 5) Wire Entry
 - 0 90D wire inet (Vertical)
 - 1 180D wire inet (with cover) (Horizontal)
 - 2 180D wire inet (without cover) (Horizontal)
 - 3 90D wire inet (Vertical)-solid block
 - 4 180D wire inet (with cover) (Horizontal)-solid block
 - 5 180D wire inet (without cover) (Horizontal)-solid block
- Four alphanumeric digits